

INTRODUCING

THE HOTUN SF DRY TRAP TUNDISH

From the manufacturer behind the revolutionary hotun dry trap tundish comes the **NEW Speedfit** range. This product eliminates the need for external discharge by allowing the T&P valve to connect directly to the internal waste or soil pipe.

The **hotun SF** range features John Guest Speedfit inlet connection.



hotun SF

Specification:

- > 15mm Speedfit x 22mm Comp
- > 22 l/min Max Flow Rate
- > 16 l/min Rated Flow Rate
- > Suitable For: Small Unvented



Part Numbers:

- 231-597-0005 - Black SF
- 231-597-0006 - White SF
- 231-551-0002 - Shield

hotun hiflo SF

Specification:

- > 15mm Speedfit x 32mm Universal/Pushfit
- > 45 l/min Max Flow Rate
- > 25 l/min Rated Flow Rate
- > Suitable For: Large Unvented & Boiler



Part Numbers:

- 231-597-0005 - Black SF
- 231-597-0006 - White SF
- 231-551-0002 - Shield

hotun XLSF

Specification:

- > 22mm Speedfit x 32mm Universal/Pushfit
- > 54 l/min Max Flow Rate
- > 40 l/min Rated Flow Rate
- > Suitable For: Universal



Part Numbers:

- 231-597-0901 - White XLSF

Features:

- > Allows the PRV discharge to be compliantly connected to drain without odours
- > Innovative combined Tundish & dry-trap
- > Eliminates the need for external discharge
- > Features JG Speedfit inlet connection
- > Connects directly to internal waste or soil pipe
- > Approved for use by many major companies
- > Simple, easy to install solution
- > Shield suitable for use on hotun hiflo sf in conjunction with a boiler
- > 5 Year Guarantee
- > WRAS Approved